

## BLU-C

Battery dischargers



BLU300C, BLU500C

Banks up to 800 V DC with total discharge down to 0 V

## BLU-C

Battery load unit and capacity tester

amperis


[www.amperis.com](http://www.amperis.com)

 C/ María Barbeito, 14  
27003, Lugo, Spain

 Contact

T [+34] 982 20 99 20  
[info@amperis.com](mailto:info@amperis.com) | [www.amperis.com](http://www.amperis.com)

## Product overview



BLU200C, BLU400C, BLU600C, BLU700C

Front panel: 7-inch touch screen and current and sense terminals

### Nine models up to 800 V

From the BLU100C to the BLU800C, the series discharges lead-acid, Li-ion, Ni-Cd or other chemistry strings with up to 300 A and 42.0 kW. The test is followed in real time on the 7-inch touch screen, with voltage and capacity graphs, and resumes by itself after a mains interruption.

### Four modes plus load profiles

Constant current, power, resistance or voltage, plus programmable profiles that reproduce real duty cycles. With the current probe, the bank is tested without taking it out of service while the total current or power is kept constant.

### Main features

- Optional total discharge down to 0 V; with the ZVD module, at constant current up to 60 or 120 A.
- Parallel operation of up to 10 identical units (from the BLU300C).
- Cell supervision with CVM/CVM-4 modules (from the BLU300C).
- Current adjustable with 0.1 A resolution.
- External BXL loads to extend the capacity.
- Adjustable alarms and shutdown against excessive discharge.
- Internal memory with USB download; optional Ethernet and RS232.



C/ María Barbeito, 14  
27003, Lugo, Spain

### Contact

+T [+34] 982 20 99 20  
info@amperis.com | www.amperis.com

# Applications and software



Capacity test on a stationary battery bank

## Applications

- Power plants and substations.
- Telecommunication systems and data centres.
- Generator excitation systems.
- Protection and control systems.
- Complete discharge of banks before recycling.

## PC software for control and analysis

The included PC software controls and observes the test over USB, presents the key parameters numerically and graphically, accepts extra alarms on cell voltage or capacity and builds reports in Excel, PDF or Word with image import.

## A complete discharge system

The cell modules connected to the unit show cell and intercell voltages on screen, the handheld voltage recorder complements the measurement with temperature and density via Bluetooth, and the ZVD module finishes the total discharge by short-circuiting the remaining energy.



C/ María Barbeito, 14  
27003, Lugo, Spain

## ✉ Contact

+T [+34] 982 20 99 20  
info@amperis.com | www.amperis.com

## BLU-C — MEASUREMENT DATA

|                             |                                                                                                     |
|-----------------------------|-----------------------------------------------------------------------------------------------------|
| Internal voltage            | 0 – 300 V DC (BLU100C-400C); 0 – 500 V (BLU500C/600C); 0 – 570/700/800 V by model; 0.1 V resolution |
| Voltage accuracy            | ±0.5% of reading ±0.1 V (0 – 800 V DC)                                                              |
| Internal current            | 0 – 300 or 0 – 400 A DC by model; 0.1 A resolution                                                  |
| Current with external probe | 0 – 2999.9 A DC; ±(0.5% + 0.2 A); ripple max ±0.4 A                                                 |
| Cell measurement (modules)  | ±50 mV, ±1 V and ±30 V DC; down to ±(0.1% + 0.1%)                                                   |
| Constant resistance         | 0.1 – 3000 Ω to 0.2 – 8000 Ω by model; ±1%                                                          |
| Time                        | ±0.1% of reading ±1 digit; up to 23 h 59 min                                                        |
| Display ranges              | 0 – 999.9 V; 0 – 2999.9 A; 0 – 9999.9 Ah                                                            |

Cell voltage sampling at 10 Hz; values are stored when the change exceeds 10 mV.  
Specifications valid at +25 °C with recommended accessories.



C/ María Barbeito, 14  
27003, Lugo, Spain



### Contact

+T [+34] 982 20 99 20  
info@amperis.com | www.amperis.com

## BLU-C – TECHNICAL SPECIFICATIONS

|                           | BLU100C | BLU200C | BLU300C | BLU400C | BLU500C | BLU570C | BLU600C | BLU700C | BLU800C |
|---------------------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| <b>Max. current</b>       | 150 A   | 300 A   | 270 A   | 300 A   | 270 A   | 100 A   | 300 A   | 260 A   | 100 A   |
| <b>Max. voltage</b>       | 300 V   | 300 V   | 300 V   | 300 V   | 500 V   | 570 V   | 500 V   | 700 V   | 800 V   |
| <b>Max. power</b>         | 20 kW   | 42 kW   | 20 kW   | 42 kW   | 20 kW   | 32 kW   | 42 kW   | 42 kW   | 32 kW   |
| <b>Cell supervision</b>   | —       | —       | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     |
| <b>Parallel operation</b> | —       | —       | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     |
| <b>Weight</b>             | 18.9 kg | 28.5 kg | 18.9 kg | 28.5 kg | 18.9 kg | 20.8 kg | 28.5 kg | 28.0 kg | 20.8 kg |

Dimensions: 564 × 267 × 355 mm (BLU100C, BLU300C, BLU500C); 615.5 × 287 × 566 mm (BLU200C, BLU400C, BLU600C, BLU700C); 560 × 268 × 473 mm (BLU570C, BLU800C). Supply 90 – 264 V AC, 50/60 Hz; input power 200 W (400 W with cell supervision).

The maximum current shown is the one maintainable over the whole voltage range; the maxima per voltage band appear on the measurement data page. Test standards: IEEE 450-2010, IEEE 1188-2005, IEEE 1106-2015, IEC 60896-11/21. Specifications valid at +25 °C.



C/ María Barbeito, 14  
27003, Lugo, Spain



**Contact**

+T [+34] 982 20 99 20  
info@amperis.com | www.amperis.com