



Rapidox 3100Z Multigas Analyser

RAPIDOX 3100Z

The Rapidox 3100-Z range includes precision single, dual and triple gas analysis instruments providing powerful functionality and extensive features. Designed for process, research and development applications, this gas analyser range has proven very popular with universities and research institutes worldwide.



www.amperis.com

AMPERIS PRODUCTS, S.L.

C/Barbeito María, 14
27003, Lugo, España

CONTACT

+T [+34] 982 20 99 20 | F [+34] 982 20 99 11
info@amperis.com | www.amperis.com



Typical gas analysis configurations include a combination of oxygen and another gas. However, other compatible gas sensors arrangements can be specified. Measurable gases include oxygen (O₂), carbon dioxide (CO₂), carbon monoxide (CO), hydrogen (H₂), moisture (H₂O), ethylene (C₂H₄), chlorine (Cl₂), methane (CH₄), nitrous oxide (N₂O), nitric oxide (NO), ammonia (NH₃), sulfur dioxide (SO₂) and ozone (O₃) to suit the application.

The flow of test gas can be adjusted with the flow gauge/needle valve on the front panel. An optional powerful long-life pump draws a gas sample at a flow rate set by the user between 0-1 litres per minute. Alternatively, the pump can be independently switched off and the unit operated under flowing gas conditions.

Standard features on all models include four fully programmable alarm circuits (volt free contacts), programmable analogue outputs (0-10V and 4-20mA) for each sensor, easy calibration (user selectable gases), RS232 / RS485 / ModBus-RTU communications and complete datalogging software. A type K thermocouple input and sensor are included for independent temperature measurements up to 1250°C, with readings displayed and data logged simultaneously with the gas analysis.

Please contact Amperis for further information or to discuss your requirements.



Though highly configurable to suit individual customer requirements, the Rapidox 3100Z range possesses a number of standard features to enhance functionality.

- Bespoke sensor combination
- Fully configurable software
- Fast and accurate response
- Simple calibration procedure
- Fully programmable outputs
- Data logging
- Type K thermocouple
- Four programmable alarms
- Operates on worldwide mains voltage
- Password protection

AMPERIS PRODUCTS, S.L.

C/Barbeito María, 14
27003, Lugo, España

CONTACT

+T [+34] 982 20 99 20 | F [+34] 982 20 99 11
info@amperis.com | www.amperis.com

Applications



Biogas



Chemicals



Combustion



Food



Gas



Glove Boxes



Inert Gas Blanketing



Manufacturing



Medical & Pharmaceutical



Metal Heat Treatment



Research & Development



Syngas

Accessories



1



2



3



4



5



6

1. Calibration Kit
2. Multiplex Sampling System
3. Gas Recovery Bag
4. Filters
5. Calibration Service
6. Peli Case

AMPERIS PRODUCTS, S.L.

C/Barbeito María, 14
27003, Lugo, España

CONTACT

+T [+34] 982 20 99 20 | F [+34] 982 20 99 11
info@amperis.com | www.amperis.com

Specification	
Oxygen Sensor	10E ⁻²⁰ ppm-30% zirconia sensor. ±1% accuracy
Other Gas Sensor	For other sensors, see the sensor matrix
Temperature Sensor	0-1250°C range Type K thermocouple, ±1°C accuracy
Max Gas Temperature	60°C
Ambient Operating Pressure	900mbar to 1100mbar absolute
Ambient Operating Temperature	5°C to 35°C
Warm-up Time	2-5 minutes at 20°C as standard
Voltage	90-260 VAC, 50/60Hz
Voltage Outputs	0-10V linear, user programmable
Current Outputs	4-20mA linear, user programmable
Digital Outputs	RS232 (RS485 option available): ModBus-rtu protocol data streamed on demand
Sample Connections	4mm ID / 6mm OD nipple type Rectus or Swagelock Front positioned
Display	Four line OLED display
Analyser Dimensions	150mm (H) x 350mm (W) x 263mm (D)
Weight	5kg as standard
Pump Option	0-1 litres per minute, user selectable

AMPERIS PRODUCTS, S.L.

C/Barbeito María, 14
27003, Lugo, España

CONTACT

+T [+34] 982 20 99 20 | F [+34] 982 20 99 11
info@amperis.com | www.amperis.com

Rapidox 3100 Sensor Matrix

Gas	O ₂	CO ₂	CH ₄	CH ₄	H ₂ O	CO	CO	Cl ₂	NO ₂	C ₂ H ₄	N ₂ O	H ₂ S	He/H ₂	NH ₃	SO ₂	SO ₂	TC
Sensor Type	Zr	IR	IR	TLD	CAP	IR	EC	EC	EC	IR	IR	EC	TCD	EC	EC	IR	Type K
Life span (mth)	24	>60	>60	>60	>36	>60	24	12	12	>60	>60	24	>60	24	24	>60	>36
Cal. (mth)	12	12	12	12	12	12	12	6	6	12		12	12	12	12	12	N/A
0-100%																	
0-80%																	
0-60%																	
0-50%																	
0-30%																	
0-20%																	
0-10%																	
0-5%																	
0-3%																	
0-2%																	
0-1%																	
0-5,000ppm																	
0-3,000ppm																	
0-2,500ppm																	
0-2,000ppm																	
0-1,000ppm																	
0-500ppm																	
0-250ppm																	
0-200ppm																	
0-100ppm																	
0-60ppm																	
0-50ppm																	
0-20ppm																	
0-10ppm																	
-65°C to +20°C																	
-100°C to +20°C																	
0 to 1250 °C																	

AMPERIS PRODUCTS, S.L.

C/Barbeito María, 14
27003, Lugo, España

CONTACT

+T [+34] 982 20 99 20 | F [+34] 982 20 99 11
info@amperis.com | www.amperis.com

AMPERIS PRODUCTS, S.L.

C/Barbeito María, 14
27003, Lugo, España

CONTACT

+T [+34] 982 20 99 20 | F [+34] 982 20 99 11
info@amperis.com | www.amperis.com